

0721-004R1  
1.30.18

**Safety** <sup>1st</sup>  
**onBoard™ 35 LT**  
Infant Car Seat


4-35 lb (1.8-15.9 kg) and 32 in. (81.3 cm) or less

When installing with a base, only use this car seat  
with a compatible onBoard 35 LT base.

For more information  
go to [safety1st.com/car-seat-base](http://safety1st.com/car-seat-base)

KEEP INSTRUCTIONS  
FOR FUTURE USE.

Read all instructions  
before using this  
child restraint.



**Safety** <sup>1st</sup>



To see installation videos, scan the QR Code

©2017 Dorel Juvenile.

**⚠ WARNING:**

Failure to follow the warnings on the labels and in the  
instruction manual can result in serious injury or death  
to your child.

Your child's height, weight, and age determine how your child restraint should be placed in the vehicle.


Children up to 1 year of age must ride rear facing.

The American Academy of Pediatrics recommends that children should remain rear facing until they are at least 2 years old.

Please talk to your doctor about the best option for your child.

**This child restraint must always be used rear facing.**

**⚠ WARNING:** Verify your child's weight and height (do not guess) before using the child restraint.




## Table of Contents

|                                                                                     |                                                                                                                                    |           |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|-----------|
|    | <b>Getting Started.....</b>                                                                                                        | <b>1</b>  |
|                                                                                     | Parts of the Child Restraint.....                                                                                                  | 1         |
|                                                                                     | Prepare Child Restraint to Fit Your Child .....                                                                                    | 4         |
|                                                                                     | How Does Your Child Fit? .....                                                                                                     | 5         |
|                                                                                     | Changing Position of Buckle .....                                                                                                  | 6         |
|                                                                                     | Changing Position of Shoulder Harness Strap .....                                                                                  | 8         |
|                                                                                     | Harness System Adjustment for Smaller Infants .....                                                                                | 10        |
|                                                                                     | Securing Child in Child Restraint.....                                                                                             | 13        |
|    | <b>General Use .....</b>                                                                                                           | <b>16</b> |
|                                                                                     | Removing and Installing to Base .....                                                                                              | 16        |
|                                                                                     | Adjusting the Base .....                                                                                                           | 17        |
|                                                                                     | Carrier Use .....                                                                                                                  | 18        |
|                                                                                     | Removing Harness System .....                                                                                                      | 19        |
|                                                                                     | Removing Seat Pad for Cleaning.....                                                                                                | 22        |
|                                                                                     | Installing Harness System .....                                                                                                    | 24        |
|                                                                                     | Canopy Use and Removal.....                                                                                                        | 27        |
|                                                                                     | Accessories on Select Models .....                                                                                                 | 29        |
|  | <b>Safety Information.....</b>                                                                                                     | <b>30</b> |
|                                                                                     | Child Restraint Use .....                                                                                                          | 30        |
|                                                                                     | Installation in Vehicle .....                                                                                                      | 30        |
|                                                                                     | Vehicle Seating Position .....                                                                                                     | 31        |
|  | <b>Vehicle Information .....</b>                                                                                                   | <b>32</b> |
|                                                                                     | Choosing Lower Anchor Belt or Vehicle Belts .....                                                                                  | 32        |
|                                                                                     | Knowing Your Vehicle Belts.....                                                                                                    | 34        |
|                                                                                     | Aircraft Information .....                                                                                                         | 37        |
|  | <b>Rear Facing with Base .....</b>                                                                                                 | <b>38</b> |
|                                                                                     |  Lower Anchor Belt Installation with Base ..... | 39        |
|                                                                                     |  Vehicle Belt Installation with Base .....      | 43        |
|  | <b>Rear Facing without Base.....</b>                                                                                               | <b>47</b> |
|                                                                                     |  Vehicle Belt Installation without Base .....   | 48        |
|  | <b>Important Information.....</b>                                                                                                  | <b>51</b> |
|                                                                                     | Using a Locking Clip .....                                                                                                         | 51        |
|                                                                                     | Dorel Juvenile Group Information.....                                                                                              | 53        |
|                                                                                     | Registration and Safety Notices .....                                                                                              | 54        |
|                                                                                     | Troubleshooting.....                                                                                                               | 55        |
|                                                                                     | Replacement Parts Order Form.....                                                                                                  | 66        |
|                                                                                     | Warranty.....                                                                                                                      | 58        |

## Parts of the Child Restraint


Front View



- A. Carry Handle**
- B. Canopy**
- C. Head Rest**  
(see page 29)
- D. Vehicle Belt Path Guide**  
(when used without the base)
- E. Adjustable Base**


- F. Harness Release Lever**  
(through opening in pad)
- G. Harness Adjustment Strap**
- H. Recline Foot Release Button**

Back View



- I. Carry Handle Adjustment Button**
- J. Rear-Facing Level Line**

- K. Shell (child restraint)**
- L. Base Release Handle**




Harness System Detail


- M. Shoulder Harness Slots**
- N. Chest Clip**
- O. Harness Strap**
- P. Buckle**
- Q. Hip Harness Slots**
- R. Buckle Slots**

## Prepare Child Restraint to Fit Your Child

Bottom of Child Restraint




- A. Base Release Handle
- B. Shoulder Harness Slots
- C. Stroller Attachment Pins
- D. Harness Strap
- E. Splitter Plate
- F. Harness Adjustment Strap
- G. Instruction Manual Storage
- H. Buckle's Metal Retainer




Top of Base

- I. Base Belt Path
- J. Lock Bars
- K. Lower Anchor Belt
- L. Base Alignment Slots
- M. Lower Anchor Belt Storage




### 1. Fully Loosen Harness Straps

Push down on harness release lever (through opening on front of seat pad) while pulling out on harness straps as shown.




### 2. Unbuckle Harness

Press in on the red button.  
Pull buckle tongues out.



### 3. Release Chest Clip

Press on chest clip release button and pull apart.



### 4. Place Child in Child Restraint to Determine Proper Harness Fit


The child's bottom and back should be flat against the child restraint.

**See page 5 for fit guidelines.**

## How Does Your Child Fit?

Use the guidelines below to determine if the buckle and harness strap are in the right place for your child.

### REAR FACING



#### Buckle Position

Start in the 1st slot and adjust outward as your child grows.

Buckle should be used in the slot closest to your child. It should not be underneath or behind your child.



#### Harness Strap Position

Always choose the shoulder harness slots that are closest to your child's shoulder height.

Harness strap **MUST** be **at or slightly below** shoulders.


If the lowest shoulder harness slots are above the child's shoulders, **do not** use this child restraint.

To change buckle position, see pages 6-7.

To change harness strap position, see pages 8-9.


To adjust harness system for smaller infants, see pages 10-12.

## Changing Position of Buckle




### 1. Unbuckle Harness

Press in on the red button.  
Pull buckle tongues out.




### 2. Turn Seat Over

Locate buckle's metal retainer on bottom of shell.



### 3. Rotate Metal Retainer and Push It Up Through Shell and Pad



### 4. From Top of Seat, Pull Buckle Out of Shell and Pad


*continued on next page*

## Changing Position of Shoulder Harness Strap




### 5. Insert Buckle's Metal Retainer into Slot Closest to Child

Buckle **MUST** face out.




### 1. Fully Loosen Harness Straps

Push down on harness release lever (through opening on front of seat pad) while pulling out on harness straps as shown.



### 6. Pull Metal Retainer Completely Through Pad and Shell




### 2. From Back of Seat, Remove Harness Strap Loops From Splitter Plate



### 7. Check Buckle


Pull up on buckle to make sure it is secured.

The buckle **MUST** not pull out.




### 3. Pull Harness Strap Out of Shoulder Harness Slots

**⚠ WARNING:** Failure to place buckle's metal retainer completely through pad and shell can result in serious injury or death.



### 4. Rethread Harness Strap Into Correct Shoulder Harness Slots For Your Child

## Harness System Adjustments for Smaller Infants




### 5. Attach 1st Harness Strap Loops to Splitter Plate

Sewn ends of the harness strap loops **MUST** face towards you.

**DO NOT** twist harness strap or harness adjustment strap.

Make sure the **same** harness strap loops are fitted **COMPLETELY ON** both sides of the splitter plate.




**⚠ WARNINGS:** Make sure that the harness height is correct for your child's size.



Do not use this child restraint rear unless the top of your child's head is at least 1 in. (2.5 cm) below the top of the child restraint.

Failure to follow these steps can result in serious injury or death.




### 1. With Buckle in the 1st Slot As Shown, Turn the Seat Over


If you need to move the buckle to the 1st slot, see pages 6-7.



### 2. From Bottom of Seat, Pull Metal Retainer Towards You and Push It Up into 2nd Slot As Shown




### 3. From Top of Seat, Lift Pad Up and Lay the Metal Retainer Flat Against the Shell As Shown



### 4. Replace Pad and Check Buckle

Pull up on buckle to make sure it is secured.

The buckle **MUST** not pull out.




### 5. Fully Loosen Harness Strap

Push down on harness release lever (through opening on front of seat pad) while pulling out on harness straps as shown.



### 6. From Back of Seat, Remove Harness Strap Loops From Splitter Plate



### 7. Pull Harness Strap Out of Shoulder Harness Slots



### 8. Rethread Harness Strap Into Correct Shoulder Harness Slots For Your Child




### 9. Attach 2nd Harness Strap Loops to Splitter Plate

Sewn ends of the harness strap loops **MUST** face towards you.

**DO NOT** twist harness strap or harness adjustment strap.

Make sure the **same** harness strap loops are fitted **COMPLETELY ON** both sides of the splitter plate.



**⚠ WARNINGS:** Make sure that the harness height is correct for your child's size.




Do not use this child restraint unless the top of your child's head is at least 1 in. (2.5 cm) below the top of the child restraint.

Failure to follow these steps can result in serious injury or death.



## Securing Child in Child Restraint



### 1. Place Child in Child Restraint

The child's bottom and back should be flat against the child restraint.

Position harness strap over child's shoulders and upper thighs.



### 2. Buckle Harness


Push buckle tongues into buckle until you hear them "click."

Pull up on harness strap to make sure buckle is locked.




### 3. Close Chest Clip

Insert right half of chest clip into left half and snap together.




### 4. Tighten Harness

Pull on harness adjustment strap to tighten harness snugly.



### 5. Position Chest Clip

The chest clip must be placed at mid-chest (even with armpits) and away from the child's neck.



### 6. Check Harness Tightness

Try to pinch the harness at the shoulders vertically between index finger and thumb as shown.

**If your fingers slip off**, the harness is tight enough.

**If you can pinch the harness strap**, tighten more. The harness straps should be snug throughout their length.

A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.

## Removing and Installing Child Restraint to Base



**⚠ WARNINGS:** Failure to fasten and tighten the harness system correctly may allow the child to be ejected from the child restraint in a crash or sudden stop causing serious injury or death.

Do not mistake comfort for safety. Harness system must be snugly adjusted.




**DO NOT** put snowsuits or bulky garments on your infant when placing them in the child restraint.

Bulky clothing can prevent the harness straps from being tightened properly.


### To Remove Child From Child Restraint:

1. Loosen Harness Strap
2. Unbuckle Harness
3. Release Chest Clip
4. Remove Child



### To Remove Child Restraint from Base


From the back of the child restraint, slide the base release handle up and lift the child restraint out of the base.



### To Attach Child Restraint to Base

Align the slots on the side of child restraint with the lock bars in the base.

Push down firmly on the carry handle and front of the child restraint to lock it to the base. You will hear a “click” when it is locked.




Pull up on front two corners of child restraint by infant's feet to make sure it is locked to the base.

**⚠ WARNINGS:** When installing with a base, only use this car seat with a compatible onBoard 35 LT base. Failure to use a correct base can cause serious injury or death.

Failure to securely attach child restraint to base can result in serious injury or death.





## Adjusting the Base




### To Lower the Base Foot

Push in on the foot release button and pull the foot all the way down.



Lock the foot on the release button as shown.




### To Store Base Foot

Pull the foot down and press in on the release button.

Push the foot up into the base to the locked position.

## Carrier Use



### To Adjust Carry Handle

Squeeze both adjustment buttons on each side of the carry handle.

Rotate up or down to desired location. Release buttons.

Make sure both carry handle adjuster buttons are in the locked position.



**Carry handle **MUST** be upright AND locked when carrying and when installed in the vehicle.**

**⚠ WARNING: DO NOT use in the seating area or across the top of shopping carts.**

## ⚠ WARNING:

Read ALL instructions before using child restraint as a carrier.

**NEVER** use carrier unless child is properly secured.

Use only as a carrier by children weighing 4-35 pounds (1.8-15.9 kg) and 32 inches (81.3 cm) or less.

**NEVER** leave child unattended. Always keep child within arm's reach.

**Suffocation Hazard:** Infant carrier can roll over on soft surfaces and suffocate child. **NEVER** place carrier on beds, sofas or other soft surfaces.

**Strangulation Hazard:** Children have **STRANGLED** in loose or partially buckled harness straps. Fully restrain the child even when carrier is used outside the vehicle.


**Fall Hazard:** Child's movement can slide carrier. **NEVER** place carrier near edges of counter tops, tables or other elevated surfaces.

Do not use the carrier if it is damaged or broken, or if any parts are missing.



## Removing Harness System

Only remove the harness system to clean the seat pad.  
To remove accessories, see page 29.




### 1. Fully Loosen Harness Strap


Push down on harness release lever (through opening on front of seat pad) while pulling out on harness straps as shown.




### 2. From Back of Seat, Remove Harness Strap Loops From Splitter Plate



### 3. Pull Harness Strap Out of Shoulder Harness Slots




### 4. Unthread Chest Clip




### 5. Unthread Buckle

Do not unbuckle the buckle.




### 6. Pull Harness Strap Out of Seat



### 7. Turn Seat Over

Locate buckle's metal retainer on bottom of shell.

## Removing Seat Pad for Cleaning




- 8. Rotate Metal Retainer and Push It Up Through Shell and Pad**



- 9. From Front of Seat, Pull Buckle Out of Shell and Pad**



You must remove the harness system in order to remove the pad. See pages 19-21.



- 1. Release the Pad Tabs**

Pull down on the pad and pull the tab out of the shell.


Repeat for other side.




- 2. Remove the Elastic Straps**


Pull the elastic strap off of the belt path guide as shown on both sides.

Repeat for other side.





**3. Pull Pad off Tabs from Top of Shell**



**4. Remove Pad from the Bottom of Shell**

Remove pad from shell.

**⚠ WARNINGS:** Do not use child restraint without the seat pad. Failure to do this can result in serious injury or death.

### Cleaning Pad and Accessories

Machine wash separately with cold water on a gentle cycle. Do not use bleach. Tumble dry separately for 10-12 minutes on low heat. Remove immediately.

**To clean canopy,** hand wash using warm sudsy water. Line dry.

### Cleaning Harness Strap


Spot clean using warm sudsy water and damp cloth.

### Replacing Pad

Starting from top of child restraint, slip pad on shell. Push pad tabs at top of shell through slots in pad. Pull harness adjustment strap through slot in pad. Wrap pad around bottom of shell.


Attach the tabs on the sides to shell. Attach elastic straps to the belt path guide.

Install harness system. See pages 24-26.



**1. Insert Buckle's Metal Retainer into Slot Closest to Child**

Buckle **MUST** face out.




**2. Pull Metal Retainer Completely Through Pad and Shell**




**3. Check Buckle**

Pull up on buckle to make sure it is secured.


The buckle **MUST** not pull out.




**4. Rethread Harness Strap**  
With sewn end of harness strap loop facing the buckle, thread harness strap down through hip harness slot.



**5. Pull Up Front of Seat Pad**





**6. Weave Harness Strap In and Out of Shell As Shown**




**7. Make Harness Strap Even**

Sewn ends of harness strap loops **MUST** face each other.




**8. Thread Buckle and Chest Clip**

Harness strap ends go through the back of buckle tongues and through the chest clip front to back as shown.



**9. Thread Harness Strap into Correct Shoulder Harness Slots For Your Child**




**10. Attach 1st Harness Strap Loops to Splitter Plate**

Sewn ends of the harness strap loops **MUST** face towards you.

**DO NOT** twist harness strap or harness adjustment strap.



Make sure the **same** harness strap loops are fitted **COMPLETELY ON** both sides of the splitter plate.



**⚠ WARNINGS:** Harness system must be installed correctly. Failure to follow these steps can result in serious injury or death.



## Canopy Use and Removal



### To Adjust Canopy


Grasp the front or sides of the canopy hoop and move it front to back to desired location.

### To Clean Canopy


Hand wash using warm sudsy water. Line dry.

### To Remove Canopy

#### 1. Undo Fastening Strip on the Back of the Shell




#### 2. Expose Canopy Hoop Connection in the Middle of the Hoop by Sliding Canopy Fabric to One Side of the Shell




#### 3. Undo Canopy Hoop

Pull top of the canopy hoop up and the bottom down where they connect.



Then pull the hoop apart and pull the canopy fabric off of the hoop.



Reverse to put back together.



## Accessories on Select Models



### Head Rest

**To remove head rest**, unbuckle the harness. Pull the buckle down through the slot in head rest. Slide head rest out from behind the harness straps.

## Child Restraint Use



Never take your child out of the child restraint while the vehicle is moving.

Never leave child unattended.

Placing your child in a hot child restraint may result in burns.

Do not use a child restraint with damaged or missing parts.

Do not use cut, frayed or damaged harnesses.

Do not substitute parts or try to modify the child restraint in any way.

Do not lubricate buckles and fasteners.

Do not use any child restraint accessory except those approved by Dorel Juvenile Group.

Never allow any child to play with this child restraint; it is not a toy.

Do not remove or cover up any of the warning labels or other labels on the child restraint.

Read all instructions for additional warnings.

On the side of the child restraint there is a date of manufacture label. Do not use this child restraint more than 8 years after the date of manufacture.

When installing with a base, only use this car seat with a compatible onBoard 35 LT base. Failure to use a correct base can cause serious injury or death.

### Installation in Vehicle

Check the vehicle belt or lower anchor belt before each use. Use only if the belt is tightened properly and locked securely in place.

This child restraint should be securely belted in the vehicle even when not in use. In a crash or sudden stop, an unsecured child restraint could injure occupants.

Do not use a child restraint that has been in a crash. You must get a new child restraint.



## Vehicle Seating Position



**Never place a child rear facing in a seating position with an active frontal air bag.**

Check the vehicle owner's manual for more information about air bag/child restraint use.



**Use the child restraint only on vehicle seats that face forward.**



**Do not use on seats that face the sides or rear of the vehicle.**

**Use the center seating position if possible.**

**For vehicles without a back seat, refer to your vehicle owner's manual.**

If you are not sure where to place the child restraint in your vehicle, consult your vehicle owner's manual, contact Dorel Juvenile Group Consumer Care Department, or visit your local Child Passenger Inspection Station. Go to <http://www.safercar.gov/cpsApp/cps/index.htm> to find your closest station.



**Children are safer when properly restrained in rear seating positions than in the front seating positions.**

**According to National Highway Traffic Safety Administration information, children in rear seating positions are statistically safer, whether you have air bags, advanced air bags, or no air bags at all.**

**To avoid your child being seriously burned, take the following precautions:**


1. Park in the shade or where sun does not directly hit the child restraint.
2. Cover the child restraint with a sheet or blanket when not in use.
3. Check for hot seat and buckles before placing child in child restraint.

To help protect your vehicle seat's upholstery from damage, use a single layer towel underneath and behind child restraint.

## Choosing Lower Anchor Belt or Vehicle Belts



Your vehicle's features may be considerably different than those pictured here.



### The LATCH System

The lower anchors of LATCH (Lower Anchors and Tethers for Children) is a universal system for installing child restraints without using vehicle seat belts.



The lower anchor system can **ONLY** be used in vehicles that have the lower anchor bars installed and designated LATCH seating positions. Most vehicles manufactured after September 2002 are equipped with lower anchor bars.


Check your vehicle owner's manual to see which seating positions may be equipped with the LATCH system.

**When installing this child restraint with vehicle belts, the lower anchor hooks and belt **MUST** be properly stored.**

**To store the lower anchor belt on this child restraint:**

Attach hooks to the storage attachments in base.





### Vehicle Belts


If lower anchors are not an option, you must use the vehicle seat belt system to install the child restraint.

There are some vehicle belts that will not work with a child restraint or will require special attention.

Check your vehicle owner's manual for specific instructions.

**⚠ WARNINGS:** When used correctly the lower anchor belt or vehicle belts are equally safe. Do not use both the lower anchor belt and vehicle belt at the same time.

Not all vehicle belts and seating positions will work with child restraints. Please follow the following steps to understand how to lock a child restraint with a vehicle belt.



#### 1. You MUST Review Your Vehicle Owner's Manual

Your vehicle owner's manual will let you know what vehicle belts and seating positions child restraints can be installed in.




#### 2. Determine How the Child Restraint Will Be Locked Into Place

The vehicle belt **MUST NOT** loosen after tightening.

This means there needs to be a way to lock the vehicle belt.

The ways this can be done are:

- By using the seat belt's retractor; or
- By using the seat belt's latch plate.



#### 3. Check the Retractor

Retractors pull seat belts into stored positions and lock the belt to hold passengers in place.

A retractor is most likely how you will be locking a child restraint into place.

See the next page for some common types of vehicle belt retractors that will work with this child restraint.

## Types of Retractors

### Switchable Retractor (most vehicles have this type)



This retractor can be switched to a locking mode.

You **MUST** have the retractor in the locking mode to use the seat belt with this child restraint.

**Switching to locking mode:** Slowly pull the shoulder belt all the way out, then let it go back in an inch or two.

As it goes back, in you will most likely hear a ratcheting sound.

Gently pull the belt to see if it has locked. You will not be able to pull any more belt out if the lock has engaged.

### Automatic Locking Retractor



This retractor always locks.



It will automatically lock after slowly pulling the seat belt out at least halfway and letting the belt go back into the retractor an inch or two.

### Emergency Locking Retractor


See Step 5, "Check the Latch Plates," on next page.

If the retractor does not lock, it is most likely an Emergency Locking Retractor. These retractors only lock during a sudden stop or collision.

You will need to determine if your seat belt's latch plate can lock the belt. See Step 4, "Check the Latch Plates," on next page.



Locking Latch Plate



Emergency Locking Retractor with a Sliding Latch Plate

## 4. Check the Latch Plates

Latch plates are the part of the seat belt that goes into the buckle.

Grasp the tongue of the latch plate (the part that goes inside the buckle) and pull straight out, in line with the lap belt.

If the latch plate does not slide up and down the vehicle belt, it is a **locking latch plate**.

If the latch plate slides up and down the vehicle belt, it is a **sliding latch plate**.

Sliding latch plates easily slip between the lap and shoulder portions of the belt.

If you have an Emergency Locking Retractor with a Sliding Latch Plate, you **MUST** use a locking clip to install the child restraint. See pages 51-52.

## Never Use With This Child Restraint

Emergency Locking Retractor Lap Only Belt



Inflatable Seat Belts





## Aircraft Information


This restraint is certified for aircraft use.

Install the child restraint in a window seat to avoid blocking the aisle. If the aircraft lap belt is too short, ask the flight attendant for a belt extender.


Use only on forward facing aircraft seats.

Contact the airline for their specific policies.

Some airlines may ask to see a label stating that this child restraint is certified for aircraft use.




There is an airplane certification label located on the side of this child restraint as shown.



### Rear Facing Aircraft Installation


For rear facing without base installation follow pages 48-50.

## Rear Facing with Base




**4-35 lb** (1.8-15.9 kg)


**32 in.** (81.3 cm) or less



**Lower Anchor Belt**



**Lap Belt**



**Lap/Shoulder Belt**



**⚠ WARNINGS:** Never place a child rear facing in a seating position with an active frontal airbag. This can result in serious injury or death.

This child restraint must always face the rear of the vehicle.



## Lower Anchor Belt Installation with Base


**⚠ WARNINGS:** Do not use the lower anchor belt along with the vehicle lap or lap/shoulder belt.

Check lower anchor belt before each use. Use only if the belt can be tightened properly and securely.

Do not fasten multiple lower anchor hooks on the same lower anchor bar in the vehicle.

When installing with a base, only use this car seat with a compatible onBoard 35 LT base. Failure to use a correct base can cause serious injury or death.

Failure to follow these warnings can result in serious injury or death.





1. Remove Lower Anchor Belt from Storage Location



2. Route Lower Anchor Belt Through Base Belt Path

Lower anchor belt adjuster can be on either side.

**Do not twist belt.**



3. Place Base in Vehicle Rear Facing

Center the base between the vehicle's lower anchors in the chosen seating position.

Review your vehicle owner's manual for lower anchor locations and lower anchor belt use.




4. Attach Lower Anchor Hooks to Vehicle's Lower Anchors



5. Tighten Belt

Place hand in base. Firmly push base down and back towards the vehicle seat back while pulling free end of belt to tighten.




## 6. Check Belt Tightness

Hold base at the belt path with your weakest hand.  
Push and pull from side to side.  
It should not move more than 1 in. (2.5 cm).


**If it moves more than 1 in. (2.5 cm), you can try:**

- A. Pulling the belt tighter.
- B. Reinstalling the base.
- C. Changing to a different seating location.
- D. Switching to vehicle belt installation.



## 7. Secure Child in Child Restraint


See pages 13-15.



## 8. Attach Child Restraint to Base

To attach to base, see page 16.  
Pull up on front two corners of child restraint by infant's feet to make sure it is locked to the base.

**Carry handle **MUST** be upright AND locked when installed in the vehicle.**





## 9. Check Level Line

Repeat steps 3-8 if level line is not parallel with the ground.

Adjust the base if needed. **See page 17 on how to use the base adjustment.**

**NOTE:** You may need to place a large rolled towel(s) or foam pool noodle(s) under front of base to help make level line parallel with the ground.

Check often to be sure padding is still in place and the belt is tight.




## To Release Lower Anchor Belt

### Remove shell from base.

Remove tension from the lower anchor belt by pushing down on side of base with the lower anchor belt adjuster. Then press the adjuster button to loosen belt.

Unhook from anchor by squeezing spring lever on hook, pushing hook back into the seat bight, and twisting. Then pull it out of the vehicle seat.

**Store lower anchor belt when not in use. See page 33.**






## Vehicle Belt Installation with Base

**⚠ WARNINGS:** Do not use the lower anchor belt along with the vehicle lap or lap/shoulder belt. Secure lower anchor belts to storage attachments in base when using the vehicle belts.

Check vehicle belt before each use. Use only if the belt can be tightened properly and locked securely in place.

When installing with a base, only use this car seat with a compatible onBoard 35 LT base. Failure to use a correct base can cause serious injury or death.

Failure to follow these warnings can result in serious injury or death.




1. Store Lower Anchor Belt



2. Place Base in Vehicle Rear Facing

Center the base in the chosen seating position.




3. Check if Your Vehicle Belts Will Work With This Child Restraint

This is very important because **not all vehicle belts will work with child restraints.**

Review pages 34-36 and your vehicle owner's manual to determine what kind of vehicle belt you have and how to lock a child restraint in place.



4. Route Vehicle Lap or Lap/Shoulder Belt Through Base Belt Path




5. Buckle Vehicle Belt



### 6. Tighten Belt

Place hand in base. Firmly push base down and back towards the vehicle seat back while pulling free end of belt to tighten.




### 7. Check Belt Tightness

Hold base at the belt path with your weakest hand.  
Push and pull from side to side.  
It should not move more than 1 in. (2.5 cm).


**If it moves more than 1 in. (2.5 cm), you can try:**

- A. Pulling the belt tighter.
- B. Reinstalling the base.
- C. Changing to a different seating location.
- D. Switching to the lower anchor belt installation if lower anchors are available in your vehicle.



### 8. Secure Child in Child Restraint


See pages 13-15.



### 9. Attach Child Restraint to Base

To attach to base, see page 16.  
Pull up on front two corners of child restraint by infant's feet to make sure it is locked to the base.

**Carry handle **MUST** be upright AND locked when installed in the vehicle.**




### 10. Check Level Line


Repeat steps 2-8 if level line is not parallel with the ground.

Adjust the base if needed. **See page 17 on how to use the base adjustment.**


**NOTE:** You may need to place a large rolled towel(s) or foam pool noodle(s) under front of base to help make the level line parallel with the ground.

Check often to be sure padding is still in place and the belt is tight.






**4-35 lb** (1.8-15.9 kg)  
**32 in.** (81.3 cm) or less




### 1. Secure Child in Child Restraint

See pages 13-15.



Lap Belt




### 2. Place Child Restraint in Vehicle Rear Facing

Center the child restraint in the chosen seating position.

Check the level line to see if it is parallel with the ground.

Adjust if needed.

Carry handle **MUST** be upright **AND** locked when installed in the vehicle.



Lap/Shoulder Belt



### 3. Check if Your Vehicle Belts Will Work With This Child Restraint


This is very important because **not all vehicle belts will work with child restraints.**

Review pages 34-36 and your vehicle owner's manual to determine what kind of vehicle belt you have and how to lock a child restraint in place.




**⚠ WARNINGS:** Never place a child rear facing in a seating position with an active frontal airbag. This can result in serious injury or death.


This child restraint must always face the rear of the vehicle.




**4. Route Vehicle Lap or Lap Portion of the Lap/Shoulder Belt Through Shell Belt Path As Shown**



**5. Buckle Vehicle Belt**



**6. Tighten Vehicle Belt**  
Lay your forearm across child restraint at the belt path while pulling up on belt to tighten.




**7. Check Belt Tightness**

Hold child restraint at the belt path with your weakest hand. Push and pull from side to side. It should not move more than 1 in. (2.5 cm).

**If it moves more than 1 in. (2.5 cm), you can try:**

- A. Pulling the belt tighter.
- B. Reinstalling the child restraint.
- C. Changing to a different seating location.




**8. Recheck Level Line**

Repeat steps 2-6 if level line is not parallel with the ground.

**NOTE:** You may need to place a large rolled towel(s) or foam pool noodle(s) under front of child restraint to help make the level line parallel with the ground.

Check often to be sure padding is still in place and the belt is tight.





## Using a Locking Clip

You will rarely need to use a locking clip except in some older vehicles. Built-in child restraint locking systems have been required in vehicles since 1996, and many vehicles had these features even earlier. Review pages 35-36 and your vehicle owner's manual to determine if your vehicle belts require a locking clip.

If you need a locking clip immediately, they are likely available at an auto dealership, an auto store, or where you purchased this child restraint. You can also call us at 1-800-544-1108 for one.

A locking clip will not fix all types of seat belt problems. You **MUST** have a lap and shoulder belt to use a locking clip.

**For Rear Facing installation with Base**, follow pages 43-44 Warnings and Steps 1-5 before starting locking clip installation.

**For Rear Facing installation without Base**, follow pages 48-49 Warnings and Steps 1-5 before starting locking clip installation.




### 1. Determine Locking Clip Position

Grasp both vehicle belts together just behind the latch plate to mark the position for locking clip.

Unbuckle the belt.


**NOTE:** If the latch plate ends up just at the belt path opening so you

cannot grasp the vehicle belt at the latch plate, grasp the vehicle belts on the opposite side of the child restraint, as close to the latch plate as possible.




### 2. Attach Locking Clip

Thread both portions of the vehicle belt onto the locking clip, as close to the latch plate as possible.




### 3. Position Locking Clip

It should be about 1 in. (2.5 cm) from vehicle belt's latch plate.



### 4. Rebuckle Vehicle Belt



### 5. Check Belt Tightness

Hold base or child restraint at the belt path with your weakest hand.



Push and pull from side to side.

It should not move more than 1 in. (2.5 cm).

**If it moves more than 1 in. (2.5 cm), you can try:**

**A.** Reinstalling the base or child restraint.

**B.** Changing to a different seating location.



**Recheck the level line.**

**Remove the locking clip when the seat belt is not being used with a child restraint.**

## Dorel Juvenile Group Information

Thank you for choosing this child restraint. The DJG family is committed to creating child restraints with the most comfort and convenience available today.

Remember, parents are a child's first teachers and examples. If you always buckle your seat belt, your child will think it is the natural thing to do. Make it a firm rule that the vehicle does not go until everyone is buckled up. Make no exceptions.

No one can predict if use of a child restraint will prevent injury or death in a particular crash. However, when combined with careful driving, proper use of a child restraint can lower a child's risk of injury or death in most crashes.

Your child's safety is worth the time it will take to read and follow these instructions. After reading, if you still have questions or have any concerns with this child restraint, please contact our Consumer Care Department at:

**Telephone:** 1-800-544-1108

M-TH from 8 A.M. to 6 P.M. EST  
FRI from 8 A.M. to 4:30 P.M. EST

**Mailing Address:**

Dorel Juvenile Group, Inc.  
Consumer Care Department  
P.O. Box 2609  
Columbus, IN 47202-2609

## Registration and Safety Notices

Please complete the postage-paid registration card that came with your child restraint, and send it to us. Child restraints could be recalled for safety reasons. You must register this restraint to be reached in a recall. Send your name, address, email address if available, the restraint's model number, and manufacturing date to:

**Dorel Juvenile Group, Inc.**  
**Consumer Care Department**

P.O. Box 2609  
Columbus, IN 47202-2609

or call 1-800-544-1108

For recall information, call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY: 1-800-424-9153), or go to <http://www.NHTSA.gov>.

**Consumer:** Just fill in your name, address and email. Please print (use dark ink).

Your Name \_\_\_\_\_

Your Street Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_

Model Number \_\_\_\_\_ Line Code \_\_\_\_\_ Manufacture Date \_\_\_\_\_

Model Number: AB123CDE Line Code: S1 CARSEAT Manufacture Date: 01/22/2015

L#11 B265035

**Example of model number, manufacture date, and line code.**



If you don't have the card or if your address changes, you will find the model number, manufacture date, and line code on the label located on side of shell.

## Troubleshooting

### 1. Locate a Child Safety Seat Inspection Station for hands on training on how to use your child restraint:

Visit your local Child Passenger Inspection Station or go to <http://www.safercar.gov/cpsApp/cps/index.htm> to find your closest station.

### 2. If the child restraint buckle or harness release lever sticks or you cannot get the straps tight enough around child:

DO NOT LUBRICATE. Check around lever and retractor for dropped food, sticky spilled drinks, dirt, leaves, etc. Clean with warm water and/or remove object with tweezers. If you cannot get the harness to adjust and remain tight with the buckle securely locked, do not use the child restraint.

### 3. If your harness twists:

Straighten the harness each time you put your child in the child restraint to help prevent twisting. Lock the buckle and tighten harness so it will be ready for next use.

## Replacement Parts Order Form

Complete the form. Your model number and manufacturer date code **MUST** be included on the form to ensure proper replacement parts. The codes can be found on a label on side of child restraint. Payment in U.S. dollars must accompany your order. Choose parts needed from the list on the next page. Return the form with payment to:

**Dorel Juvenile Group, Inc.**  
**Consumer Care Department**  
P.O. Box 2609  
Columbus, IN 47202-2609

Please make money orders payable to Dorel Juvenile Group, Inc. Fill in the area on the next page to charge credit card. (Visa or MasterCard **only**). We do not accept cash, personal checks, or other credit cards. All outside of U.S. and Canada **MUST** use credit card.

**Ship To:** (Please Print)

**Name:** \_\_\_\_\_

**Address:** \_\_\_\_\_

**City:** \_\_\_\_\_

**State/Province:** \_\_\_\_\_ **Zip:** \_\_\_\_\_

**Telephone:** \_\_\_\_\_

**Email Address:** \_\_\_\_\_

We **MUST** have this information:

**Model Number (8 to 9 characters):** \_\_\_\_\_

**Manufacture Date (mm/dd/yyyy):** \_\_\_\_\_

## Replacement Parts List

**NOTE:** If requested color is not available, similar color will be substituted. Prices are subject to change.

| Part                    | Cost    | Qty   | Total Cost |
|-------------------------|---------|-------|------------|
| Buckle Assembly.....    | \$7.99  | ..... | \$.....    |
| Seat Pad Set.....       | \$38.00 | ..... | \$.....    |
| Chest Clip .....        | \$1.50  | ..... | \$.....    |
| Lower Anchor Belt ..... | \$17.99 | ..... | \$.....    |
| Instructions.....       | \$0.00  | ..... | \$.....    |
| Locking Clip.....       | \$2.50  | ..... | \$.....    |

**Merchandise Total:** .....\$.....

**Shipping and handling:**.....\$.....

|                           |        |                              |         |
|---------------------------|--------|------------------------------|---------|
| Up to \$25.00 .....       | \$5.95 | \$100.01 to \$150.00 .....   | \$10.95 |
| \$25.01 to \$50.00 .....  | \$6.95 | \$150.01 to \$200.00 .....   | \$11.95 |
| \$50.01 to \$75.00 .....  | \$8.95 | \$200.01 and up.....         | \$13.95 |
| \$75.01 to \$100.00 ..... | \$9.95 | Outside Continental USA..... | \$10.00 |

**Sales Tax** .....\$.....

(Arizona, California, Georgia, Indiana, Missouri, South Carolina, and Texas residents add applicable sales tax.)

**Grand Total**.....\$.....

No shipping and handling on instructions for quantities under 6. Add \$.50 for each instruction over 6, then add applicable shipping and handling.

### Fill Out For Credit Card

☐ Visa ☐ MasterCard

**Card Exp. Date:**

**Cardholder's Name:**

**Card Number:**

**Signature:**

## Warranty

Dorel Juvenile Group, Inc. (DJG) warrants this product to the original retail purchaser as follows:

This product is warranted against defective materials or workmanship for one year from the date of original purchase. **An original receipt is required to validate your warranty.** DJG will, at its option, provide replacement parts or replace this product. DJG reserves the right to substitute if the part or model has been discontinued.

To make a claim under this warranty you may write to DJG, Consumer Care Department, P. O. Box 2609, Columbus, IN 47202-2609; or call 1-800-544-1108 from 8:00 a.m. to 6:00 p.m. EST Monday through Thursday and from 8:00 a.m. to 4:30 p.m. on Friday.

**Proof of purchase is required and shipping charges are the responsibility of the consumer.**

**Warranty Limitations:** This warranty does not include damages which arise from misuse or abuse of this product.

**Limitation of Damages:** The warranty and remedies as set forth are exclusive and in lieu of all others, oral or written, expressed or implied. In no event will DJG or the dealer selling this product be liable to you for any damages, including incidental or consequential damages, arising out of the use or inability to use this product.

**Limitation of warranties and other warranty terms and state law rights:**

Any implied warranties, including implied warranties of the merchantability and fitness for a particular purpose, shall be limited to the duration and terms of the express written warranty. Some states do not allow limitations as to how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.

This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. Neither DJG nor the dealer selling this product authorized any person to create for it any other warranty, obligation, or liability in connection with this product.



## Dash Travel System

HB2490+IC261 User Guide

Read all instructions before assembly and use. Keep instructions for future use.



©2017 Dorel Juvenile.

(800) 544-1108

Styles and colors may vary. Estilos y colores pueden variar.

Made in CHINA. Hecho en CHINA.

Made for Dorel China America, Inc.

c/o Dorel Juvenile Group, Inc.

Hecho para Dorel China America, Inc.

c/o Dorel Juvenile Group, Inc.

2525 State St., Columbus, IN 47201-7494

07/17/18 WM2490-001

## Dash Travel System

HB2490+IC261 Guía del Usuario

Lea detenidamente las instrucciones antes de armar y usar. Guarde estas instrucciones para su uso futuro.nk

### **WARNING:**

**FOR THE SAFETY OF YOUR CHILD, PLEASE READ THE FOLLOWING WARNINGS AND ASSEMBLY INSTRUCTIONS AND KEEP FOR FUTURE REFERENCE.**

- Adult assembly required. **CAUTION:** Keep small parts away from children during assembly.
- **NEVER LEAVE CHILD UNATTENDED. ALWAYS** keep child in view when in stroller.
- **AVOID SERIOUS INJURY** from falling or sliding out. **ALWAYS** use seat belt. Check frequently to make sure it is secure.
- **ALWAYS** keep fingers away from moving parts, when folding, unfolding or adjusting stroller to prevent finger entrapment.
- **ALWAYS** make sure stroller is **FULLY OPEN AND LOCKED** before using.
- **ALWAYS** use the brakes when stroller is stopped.
- **ALWAYS** remove protective material and poly bags and dispose before assembly.
- **NEVER** put hot liquids in the cup holder.
- **NEVER** use stroller on stairs or escalators.
- **NEVER** rollerblade with stroller.
- **NEVER** allow children to play with or hang onto the stroller.
- **NEVER** allow children to climb into the stroller unassisted. Stroller may tip over and injure child.
- **NEVER** place or hang parcels, bags or accessories on the handle or canopy. The stroller may tip over or the canopy may collapse.
- This product will become unstable if a parcel bag or rack is used when there is no provision for one.
- This product may become unstable if a parcel bag, other than the one recommended by the manufacturer is used.
- This product will become unstable if the manufacturer's recommended load is exceeded.
- **DO NOT** carry additional children, goods or accessories in or on this product except as recommended in the manufacturer's instructions.
- **NEVER** place more than 2 lbs. (0.91 kg) in parent's tray to prevent tipping.

### **ADVERTENCIA:**


**POR LA SEGURIDAD DE SU HIJO, POR FAVOR LEA LAS SIGUIENTES ADVERTENCIAS E INSTRUCCIONES DE ENSAMBLE, Y GUÁRDELAS PARA CONSULTA FUTURA.**

- El armado debe ser realizado por un adulto. **PRECAUCIÓN:** Durante el armado, mantenga las piezas pequeñas fuera del alcance de los niños.
- **NUNCA DEJE AL NIÑO SIN SUPERVISIÓN. SIEMPRE** mantenga al niño a la vista cuando esté en la carriola.
- **EVITE UNA LESIÓN GRAVE** por caída o resbalamiento. **SIEMPRE** use el cinturón de seguridad. Revise con frecuencia para asegurarse que esté asegurado.
- **SIEMPRE** mantenga los dedos alejados de las piezas movibles, al plegar, desplegar o ajustar la carriola, con el fin de evitar que se atrapen los dedos.
- **SIEMPRE** asegúrese de que la carriola esté **COMPLETAMENTE ABIERTA Y BLOQUEADA** antes de usarla.
- **SIEMPRE** use los frenos cuando la carriola esté parada.
- **SIEMPRE** quite el material de protección y las bolsas de plástico y deséchelos antes de ensamblar.
- **NUNCA** ponga líquidos calientes en el apoyavasos.
- **NUNCA** use la carriola en escaleras ni escaleras eléctricas.
- **NUNCA** patine junto con la carriola.
- **NUNCA** deje que los niños jueguen con ni se cuelguen de la carriola.
- **NUNCA** deje que los niños se suban a la carriola sin ayuda. La carriola podría volcarse y lesionar al niño.
- **NUNCA** coloque ni cuelgue paquetes, bolsas ni accesorios en el asa ni en la capota. La carriola podría volcarse o la capota podría colapsarse.
- Este producto se volverá inestable si se usa una bolsa de paquetes o una rejilla cuando no hay provisión para ello.
- Este producto puede volverse inestable si se usa

- **NEVER** place more than 10 lbs. (4.5 kg) in the storage basket. If weight is exceeded, hazardous unstable conditions may exist.
- **STROLLER** is only for use with children up to 50-lbs. (22.7-kg), and **WHEN SEATED**, the midpoint of the child's head is at or below the top of the stroller seat.
- **ONLY** use this stroller with **ONE** child at a time.
- **STROLLER** is for use with children who can sit up unassisted, and is **NOT** recommended for newborns.

- una bolsa de paquetes diferente a la recomendada por el fabricante.
- Este producto se volverá inestable si se excede la carga recomendada por el fabricante.
- **NO** cargue a otros niños, artículos ni accesorios dentro o sobre este producto excepto lo recomendado en las instrucciones del fabricante.
- **NUNCA** coloque más de 2 lbs. (0.91 kg) en la charola de los padres, para evitar volcaduras.
- **NUNCA** coloque más de 10 lbs. (4.5 kg) en el cesto de almacenamiento. Si el peso se excede, podrían existir condiciones inestables peligrosas.
- La carriola es sólo para niños que pesen hasta 50 libras (22.7-kg), y que **AL ESTAR SENTADOS**, el punto medio de la cabeza del niño está al nivel o más abajo que el borde superior del asiento de la carriola.
- **SÓLO** use esta carriola con **UN** niño a la vez.
- **LA CARRIOLA** debe usarse con niños que pueden sentarse sin asistencia, **NO** se recomienda para recién nacidos.

## Parts / Lista de piezas





## 1 Unfold Stroller

Use one hand to release latch **(Figure 1)** and the other hand to pull up on handlebar **(Figure 1a)**. Stroller will click when completely open and locked.

### Abra la carriola

Utilice una mano para abrir la cubierta **(Figura 1)** y la otra mano para levantar el manillar **(Figura 1a)**. Carriola hará clic cuando está completamente abierta y trabada.




## 2 Front Wheel

Slide front wheel onto frame tube as shown. Wheel will click when installed properly **(Figure 2)**.

### Ruedas delantera

Deslice la rueda delantera en el tubo del armazón. La rueda hará clic cuando quede bien instalada **(Figura 2)**.



**NOTE:** Hardware for rear wheel assembly is located on axle.

## 3 Rear Wheels

**Helpful Hint:** For ease of removal and assembly of cotter pin use needle nose pliers. Remove cotter pin and one metal washer from axle leaving one plastic washer on the axle. With the spokes facing out, slide a wheel onto the axle. Slide on a second washer (**Figure 3**).

Insert straight side of cotter pin through hole in axle (**Figure 3a**). Repeat steps on other rear wheel.

Snap hub caps onto both wheels (**Figure 3b**).

Hold the axle assembly with the brakes toward the handlebars. Push onto frame until buttons “snap” into place (**Figure 3c**).

**NOTA:** Los elementos de ferretería para el armado de las ruedas traseras se encuentran en el eje.





## Ruedas traseras

**Sugerencia útil:** Para retirar y armar fácilmente el pasador de chaveta, utilice la pinza de punta aguja. Quite el pasador de chaveta y una arandela de metal del eje de modo que quede sólo una arandela de plástico en el eje. Deslice una rueda, con los rayos hacia fuera, en el eje. Deslice la otra arandela (**Figura 3**).

Inserte el lado recto del pasador de chaveta a través del orificio del eje (**Figura 3a**). Repita el procedimiento para la otra rueda trasera.

Encaje las tapas de los cubos en ambas ruedas (**Figura 3b**).

Sostenga el ensamble del eje con los frenos hacia las asas del manubrio. Empuje contra el armazón hasta que los botones encajen en su lugar (**Figura 3c**).




#### 4 Install Canopy

Slide plastic housing on canopy mounts onto the receivers on the stroller frame (**Figure 4**). Push down firmly on each side to make sure the canopy is fully snapped into place.

##### Instale la capota

Deslice la cubierta de plástico sobre los soportes de la capota en los espacios correspondientes en el armazón de la carriola (**Figura 4**). Empuje firmemente hacia abajo de cada lado para asegurarse de que la capota quedó bien encajada.




#### 5 Attach Canopy

Pull out the straps at the lower back of the canopy, hang them to the bolts to secure canopy (**Figure 5**).

##### Coloque la capota

Tire de las correas que se encuentran en la parte inferior trasera de la capota, coloque la correas en los pernos para asegurar la capota (**Figura 5**).




#### 6 Parent's Tray

Align posts with holes on parent tray. Snap parent's tray onto handlebar tubes (**Figure 6**).

##### Charola para los padres

Alinee los puntales con los orificios en la charola para los padres. Encaje la charola para los padres en los tubos del asa del manubrio (**Figura 6**).



## 7 Child's Tray


Guide tray tabs into slots on stroller frame.  
Push until tray clicks into place.

**To remove tray**, squeeze release levers on both sides and lift tray up and off.

### Charola para el niño

Guíe las lengüetas de la charola dentro de las ranuras del armazón de la carriola. Empuje hasta que la charola encaje en su lugar con un clic.

**Para quitar la charola**, presione las palancas de liberación a cada lado, levante la charola y quítela.



## To Use / Para Uso

### 1 Brakes


**Lock Brakes:** Step down onto brake levers on both rear wheels (**Figure 1**). To park stroller, **BOTH BRAKES MUST BE LOCKED**.

**Unlock Brakes:** Lift up levers to unlock brakes.

### Frenos

**Trabe los frenos:** Pise las palancas de los frenos en las dos ruedas traseras (**Figura 1**). Para estacionar la carriola, **AMBOS FRENOS DEBEN ESTAR BLOQUEADOS**.

**Desbloquear los frenos:** Levante las palancas para soltar los frenos.



### Engage Front Swivel Lock


Slide lever up with your hand to keep dual wheel from swiveling. Step down on lever to swivel (**Figure 1a**).

**NOTE:** Locked position is ideal for travel over rocky or uneven surfaces.

### Enganche locks delanteras giratorias

Deslice la palanca hacia arriba con la mano para que las ruedas no giren. Presione la palanca que giren (**Figura 1a**).

**NOTA:** La posición de traba es ideal para llevar la carriola sobre superficies desparejas o con piedras.





## 2 Seat Position

To lower seat back completely: Lift the clamp lever (**Figure 2**) and lower seat back (**Figure 2a**). Push clamp lever closed.

**To raise seat back:** Lift clamp lever. Hold end of strap, slide clamp lever up, pushing seat forward and push clamp lever closed.

**NOTE: DO NOT** adjust the seat when your child is in the stroller.



## Posición del asiento

Para reclinar el asiento por completo: Levante el pestillo (**Figura 2**) y recline el asiento (**Figura 2a**). Cierre el pestillo.

**Para colocar el asiento en posición vertical:** Levante el pestillo. Sostenga el extremo de la correa, suba el pestillo, empuje el asiento hacia adelante y cierre el pestillo.

**NOTA: NO** ajuste el asiento cuando su niño está en la carriola.

## ⚠ WARNING

- For proper installation of the restraint system, make sure both anchors lay flat against the back board.
- NEVER** use stroller without **BOTH** restraint and crotch straps.

## ⚠ ADVERTENCIA


- Para la instalación correcta del sistema de correas, asegúrese de que ambos anclajes queden planos contra la tablilla del respaldo.
- NUNCA** utilice la carriola sin **LAS** correas de seguridad y de la entrepierna.

## 3 Adjust Restraint Height

Push each anchor through seat back and into the desired slot (**Figure 3**). Be sure anchors lay flat against seat back.

## Ajustar la altura del sistema de retención

Haga pasar los anclajes a través del respaldo del asiento, a través de la ranura deseada (**Figura 3**). Asegúrese de que los anclajes queden planos contra el respaldo del asiento.




## 4 Handlebar

Press buttons on both sides of the handlebar and rotate up or down as desired (**Figure 4**).

## Manubrio

Presione los botones a ambos lados del manubrio y gírelo hacia arriba o hacia abajo (**Figura 4**).



## 5 Restraint System

Place your child in the stroller, with the crotch strap between the child's legs. Fasten both buckles (**Figure 5**). Tighten waist and shoulder straps snugly around your child (**Figure 5a**).

### Shoulder straps:

**To tighten**, loosen strap at (A) and slide buckle up (**Figure 5b**).


**To loosen**, loosen strap at (A) and slide buckle down (**Figure 5b**).

### Waist straps:

**To tighten**, pull end (C).

**To loosen**, loosen strap at (B) (**Figure 5b**).

**NOTE:** If the straps should come out of the buckle, rethread as shown (**Figure 5b**).



## Cinturón de retención

Siente a su niño en la carriola, con la correa de la entrepierna entre las piernas y las correas del hombro sobre los hombros. Enganche ambas hebillas (**Figura 5**). Coloque las correas correspondientes a la cintura y los hombros alrededor del niño y ajústelas bien (**Figura 5a**).

**Correa de hombros: Para tensar**, aflojar la correa en (A) y deslice la hebilla hacia arriba (**Figura 5b**). **Para aflojar**, aflojar la correa en (A) y deslice la hebilla hacia abajo (**Figura 5b**).

**Correa a la cinturas: Para tensar**, tire del extremo (C) (**Figura 5b**). **Para aflojar**, aflojar la correa en (B). **NOTA:** Si las correas se salen de la hebilla, vuelva a pasar tal como se muestra (**Figura 5b**).

## ⚠ WARNING

- **NEVER LEAVE CHILD UNATTENDED. ALWAYS** keep child in view when in stroller.
- **AVOID SERIOUS INJURY** from falling or sliding out. **ALWAYS** use seat belt. Check frequently to make sure it is secure.
- Belts must be threaded exactly as shown (Figure 5b).
- Failure to follow these instructions could result in the serious injury or death of your child.

## ⚠ ADVERTENCIA

- **NUNCA DEJE AL NIÑO SIN SUPERVISIÓN. SIEMPRE** mantenga al niño a la vista cuando esté en la carriola.
- **EVITE UNA LESIÓN GRAVE** por caída o resbalamiento. **SIEMPRE** use el cinturón de seguridad. Revise con frecuencia para asegurarse que esté asegurado.
- Los cinturones deben pasarse exactamente como se muestra (Figura 5b).
- El no seguir estas instrucciones podría resultar en lesiones graves o la muerte del niño.

## 6 To Fold Stroller

**Lock rear brakes.** Remove your baby. Find LIFT TO FOLD handle under pocket on seat (**Figure 6**). Lift up on the fold handle and the stroller will collapse to folding position (**Figures 6 and 6a**).

Side lock tab will snap into place when fully locked.

Ensure lock (on left side of stroller handle) locks into place when folded, as shown (**Figure 6b**).

Stroller will stand on its own.


## Para plegar la carriola

**Ponga los frenos traseros.** Saque al bebé. Ubique la agarradera LEVANTE PARA PLEGAR que se encuentra debajo del bolsillo del asiento (**Figura 6**). Tire de la agarradera hacia arriba para que la carriola se cierre y quede plegada (**Figuras 6 y 6a**).

La lengüeta de traba lateral se va a encajar en el lugar si quedó correctamente trabada.

Asegurar la lengüeta traba lateral (que se encuentra a la izquierda del manubrio) se en el lugar correctamente trabada, como se muestra (**Figura 6b**).

La carriola se parará sola.



## 7 To Install Infant Car Seat

### Para instalar los autoasientos de bebé

#### ⚠ WARNING

To avoid serious injury:

- Use **ONLY** IC178, IC181, IC201, IC203, IC205, IC206, IC207, IC208, IC210, IC211, IC212, IC217, IC218, IC219, IC220, IC224, IC226, IC228, IC229, IC230, IC231, IC233, IC234, IC240, IC244, IC250, IC251, IC252, IC258, IC259, IC261, IC263, IC267, IC279, IC280, IC305, 22036, 22056, 22326 infant car seats with this stroller.
- Please refer to the manufacturer's instructions for the use of your infant car seat.
- **ALWAYS** use child's tray when car seat is installed.
- **NEVER** use child tray **cup holder** when car seat is attached to stroller. Stroller may tip over and injure infant.
- **ALWAYS** install car seat facing to the rear of the stroller.
- **ALWAYS** use the restraint system in the car seat.

#### ⚠ ADVERTENCIA

Para evitar lesiones graves:

- **SÓLO** use autoasientos de bebé IC178, IC181, IC201, IC203, IC205, IC206, IC207, IC208, IC210, IC211, IC212, IC217, IC218, IC219, IC220, IC224, IC226, IC228, IC229, IC230, IC231, IC233, IC234, IC240, IC244, IC250, IC251, IC252, IC258, IC259, IC261, IC263, IC267, IC279, IC280, IC305, 22036, 22056, 22326 con esta la carriola.
- Consulte las instrucciones del fabricante para el uso del autoasiento de bebé.
- **SIEMPRE** use la charola para el niño cuando el autoasiento está instalado.
- **NUNCA** use el **apoyavaso** de la bandeja para niños si el asiento para automóvil está colocado en la carriola. La carriola puede volcar y lastimar al bebé.
- **SIEMPRE** instale el autoasiento mirando hacia atrás de la carriola.
- **SIEMPRE** use el sistema de cinturones del autoasiento. El no seguir estas instrucciones podría resultar en lesiones graves o la muerte del niño.

Recline seat back to lowest position (**Figure 7**). Close canopy.


**Car seat must be positioned so child faces the stroller handle.**

Position car seat over the stroller. Touch rear flat vertical surface of car seat **A** against rear vertical surface of the child tray **B**. Lower straight down into stroller and push down on handle. Car seat will click into place when fully nested (**Figures 7a and 7b**).

Recline el respaldo del asiento a la posición más baja (**Figure 7**). Cierre la capota.

**El autoasiento debe quedar colocado de modo que el niño mire hacia la manija del carriola.**

Ubique el autoasiento en la carriola. Coloque la superficie vertical plana de la parte trasera del asiento **A** contra la superficie vertical trasera de la charola para el niño **B**. Baje hacia la carriola y jale la manija hacia abajo. El autoasiento hará "clic" en el lugar cuando encaje. El autoasiento se encajará en posición cuando esté colocado por completo (**Figuras 7a y 7b**).







**continued / continuación**

When properly installed, car seat will come to rest on child tray and stroller frame (**Figure 7c**).

Pull up on car seat to make sure it is securely installed (**Figure 7d**).

Una vez instalado correctamente, el autoasiento descansará sobre charola para el niño y el armazón de la carriola (**Figura 7c**).

Tire del autoasiento hacia arriba para asegurarse de que esté firmemente instalado (**Figura 7d**).




To remove the car seat, pull the release lever as shown (**Figure 7e**).

Lift car seat.

Para quitar el autoasiento, tire de la palanca de liberación, como se muestra (**Figura 7e**).

Levante el autoasiento.



## Replaceable Parts

- Single front wheels
  - Single rear wheels
  - Child's tray
  - Parent's tray
  - Canopy
- 
- To order parts call (800) 544-1108.
  - Include the model number and manufacture date (found on the stroller) and a brief description of the part.

## Piezas de repuesto

- Ruedas delanteras sencillas
  - Ruedas traseras sencillas
  - Charola para el niño
  - Charola para los padres
  - Capota
- 
- Para pedir piezas, llame al (800) 544-1108.
  - Incluya el número de modelo y la fecha de fabricación (se encuentra en la carriola) junto con una breve descripción de la pieza.

## Care and Maintenance / Cuidado y mantenimiento

### Stroller Care and Maintenance

- To clean stroller fabric and seat pad, use a sponge or damp cloth with cold water and mild soap. Air dry only. Do not use harsh household cleaners or bleach to clean stroller.
- Restraint and crotch straps should be surface washed and air dried only. Do not place in washing machine or dryer.
- Periodically, check for loose screws, worn parts, torn material or loose stitching. Tighten or replace parts as needed.

### Cuidado y mantenimiento de la carriola

- Para limpiar la tela de la carriola y la almohadilla del asiento utilice una esponja o paño húmedo, agua fría y jabón suave. Secar al aire únicamente. No utilice limpiadores para el hogar abrasivos o blanqueadores para limpiar la carriola.
- Las correas de retención y de la entrepierna deben limpiarse en su superficie únicamente y debe dejarlas secar al aire. No colocar en la lavadora ni en la secadora.
- De vez en cuando revise que no haya tornillos flojos, piezas desgastadas, material rasgado ni costuras sueltas. Apriete o cambie las piezas según sea necesario.

### One-Year Limited Warranty

Dorel Juvenile Group, Inc. warrants to the original purchaser that this product (Dash Travel System), is free from material and workmanship defects when used under normal conditions for a period of one (1) year from the date of purchase. Should the product contain defects in material or workmanship Dorel Juvenile Group, Inc., will repair or replace the product, at our option, free of charge. Purchaser will be responsible for all costs associated with packaging and shipping the product to Dorel Juvenile Group Consumer Relations Department at the address noted on front page and all other freight or insurance costs associated with the return. Dorel Juvenile Group will bear the cost of shipping the repaired or replaced product to the purchaser. Product should be returned in its original package accompanied by a proof of purchase, either a sales receipt or other proof that the product is within the warranty period. This warranty is void if the owner repairs or modifies the product or the product has been damaged as a result of misuse.

This warranty excludes any liability other than that expressly stated previously, including but not limited to, any incidental or consequential damages.

SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT MAY VARY FROM STATE TO STATE.

### Garantía limitada de un año

Dorel Juvenile Group, Inc. garantiza al comprador original que este producto (Sistema de viaje "Dash") estará libre de defectos de material y mano de obra cuando se utilice bajo condiciones normales durante un periodo de un (1) año a partir de la fecha de compra. Si el producto tuviese defectos de material o mano de obra, Dorel Juvenile Group, Inc. reparará o reemplazará el producto, a nuestra opción, sin cargo. El comprador será responsable de todos los costos asociados con embalar y enviar el producto al Departamento de Relaciones con el Consumidor de Dorel Juvenile Group a la dirección indicada en la primera página y de todos los otros costos de envío o seguro asociados con la devolución. Dorel Juvenile Group correrá con los gastos de enviar el producto reparado o reemplazado al comprador. El producto se debe devolver en su embalaje original acompañado de la constancia de compra, ya sea un recibo de compra u otra prueba que demuestre que el producto está dentro del periodo de garantía. Esta garantía es nula si el propietario repara o modifica el producto o si éste sufrió daño como resultado de uso incorrecto.

Esta garantía excluye cualquier responsabilidad que no sea la expresamente indicada anteriormente, incluyendo pero sin limitarse a daños incidentales o consecuentes.

ALGUNOS ESTADOS NO PERMITEN LA EXCLUSIÓN O LIMITACIÓN DE DAÑOS INCIDENTALES O CONSECUENTES, POR LO TANTO LA LIMITACIÓN O EXCLUSIÓN ANTERIOR PODRÍA NO APLICARSE EN SU CASO.

ESTA GARANTÍA LE OTORGA DERECHOS LEGALES ESPECÍFICOS Y USTED PODRÍA TENER TAMBIÉN OTROS DERECHOS QUE PUEDEN VARIAR DE UN ESTADO A OTRO.

